

✓

L5 ANSWER 56 OF 72 CA COPYRIGHT 2001 ACS
AN 107:160408 CA
TI Raw mixture for producing lightweight concrete
IN Fedynin, N. I.; Abgaryan, G. G.; Blokhina, A. K.
PA Ural Scientific-Research and Design Institute for Building Materials,
Novokuznetsk, USSR; Novokuznetsk House-Building Combine
SO U.S.S.R.
From: Otkrytiya, Izobret. 1987, (24), 92.
CODEN: URXXAF
DT Patent
LA Russian
IC ICM C04B038-02
ICS C04B028-08
CC 58-2 (Cement, Concrete, and Related Building Materials)

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	<u>SU 1320200</u>	A1	19870630	SU 1985-3981955	19851008
AB	For increased strength and accelerated hardening at neg. temps., the raw mix contains unhydrated Na silicate (with SiO2 modulus 1.2-1.6) 0.5-3 as alk. additive and Al sulfate 0.2-1.5, in addn. to <u>slag</u> portland cement 18-35, coal ash 18-22, granulated blast-furnace slag 28-42, Na secondary alkyl sulfate 0.02-0.3, and Al powder 0.005-0.03 wt.%.				
ST	sodium silicate lightwt concrete strength; aluminum sulfate lightwt concrete strength				
IT	Ashes (residues) (coal, in lightwt. concrete, with aluminum sulfate and sodium silicate for increased strength and accelerated hardening at				